

Series	Sensor	EFL	Fno	FOV (deg.)			TV-Distortion (%)		RI (%)	TT (mm)	BFL (mm)	CRA (deg.)	Outline Dimension (mm)	
	Format			H	V	D	H	V					Diameter	Thread
HPB1005	1/4"	9.30	3.1	23	18	29	-0.3	-0.5	90.5	14.198	7.008	8.2	Φ14.0	M12xP0.5
	1/3.6"	3.81	2.3	61	45	77	-5.2	-10.7	93.9	20.952	5.666	13.6	Φ14.0	M12xP0.5
HPB1014	1/3.3"	3.81	2.3	73	46	88	-4.7	-15.4	89.4	20.952	5.666	15.6	Φ14.0	M12xP0.5
	1/3"	3.81	2.3	76	56	98	-6.9	-15.9	81.6	20.952	5.666	16.8	Φ14.0	M12xP0.5
HPB1018	1/4"	1.95	2.4	114	83	153	-10.6	-30.6	97.4	18.338	4.908	14.0	Φ14.0	M12xP0.5
HPB1022	1/4"	2.47	2.4	93	68	118	-8.0	-20.0	94.0	18.105	5.470	15.8	Φ14.0	M12xP0.5
	1/3.6"	2.47	2.4	94	70	120	-8.2	-20.5	93.9	18.105	5.470	16.0	Φ14.0	M12xP0.5
HPB1025	1/4"	1.67	2.8	129	95	168	-12.0	-36.4	97.8	18.452	4.252	16.8	Φ16.0	M12xP0.5
HPB1027	1/4"	1.95	2.4	121	73	147	-7.2	-36.5	95.2	20.019	4.689	15.5	Φ14.0	M12xP0.5
HPB1033	1/3"	2.30	2.5	116	73	139	-7.0	-31.2	96.3	16.733	3.689	20.7	Φ15.0	M12xP0.5
	1/3.6"	2.30	2.5	98	73	123	-8.2	-20.8	96.2	16.733	3.689	18.8	Φ15.0	M12xP0.5
	1/4"	2.30	2.5	91	68	115	-7.5	-18.3	96.3	16.733	3.689	17.7	Φ15.0	M12xP0.5
HPB1047	1/4"	2.50	2.9	89	55	106	-4.9	-18.8	96.7	22.551	6.423	12.1	Φ17.2	M12xP0.5
	1/2.7"	2.50	2.9	135	75	157	-6.3	-45.9	76.5	22.551	6.423	18.8	Φ17.2	M12xP0.5
	1/3"	2.50	2.9	105	78	132	-8.9	-23.5	86.4	22.551	6.423	15.7	Φ17.2	M12xP0.5
	1/3.2"	2.50	2.9	106	79	133	-9.0	-23.8	86.1	22.551	6.423	15.8	Φ17.2	M12xP0.5
	1/2.8"	2.50	2.9	128	72	148	-5.0	-40.0	80.2	22.551	6.423	17.7	Φ17.2	M12xP0.5
HPB1062	1/4"	3.23	2.0	69	49	89	-15.7	-6.6	96.0	16.700	4.780	15.0	Φ14.0	M12xP0.5
HPB2010	1/4"	4.80	2.6	41	31	50	-0.4	-0.5	65.9	10.277	4.578	14.4	Φ14.0	M12xP0.5
HPB2033	1/4"	2.20	2.2	93	71	112	-6.7	-15.9	66.7	14.462	4.608	27.8	Φ15.0	M12xP0.5
HPB3041	1/3.6"	1.21	2.6	124	104	139	-6.5	-14.7	35.4	13.876	2.496	20.3	Φ15.0	M12xP0.5
	1/4"	1.21	2.6	118	98	133	-5.9	-12.7	39.0	13.876	2.496	18.4	Φ17.0	M12xP0.5
	1/6"	1.21	2.6	88	71	103	-2.6	-4.3	57.8	13.876	2.496	10.5	Φ17.0	M12xP0.5
HPB3045	1/4"	1.28	2.7	131	105	153	-10.2	-28.1	41.1	9.924	2.676	24.1	Φ14.0	M12xP0.5
	1/3"	1.28	2.7	155	130	173	NA	NA	3.4	9.924	2.676	27.4	Φ14.0	M12xP0.5
HPB3059	1/3.6"	1.11	2.2	144	117	174	-12.0	-36.2	33.8	13.307	2.122	17.7	Φ16.9	M12xP0.5
	1/4"	1.11	2.2	138	112	163	-10.7	-31.2	35.8	13.307	2.122	16.2	Φ16.9	M12xP0.5
HPB3063	1/3.6"	1.27	2.4	117	98	131	-5.1	-10.3	33.4	13.690	2.533	18.0	Φ14.3	M12xP0.5
	1/4"	1.27	2.4	117	87	128	-3.5	-10.3	36.1	13.690	2.533	16.7	Φ14.3	M12xP0.5
	1/3"	1.27	2.4	128	112	142	-6.6	-13.8	14.7	13.690	2.533	21.8	Φ14.3	M12xP0.5
HPB3071	1/3.6"	1.49	2.1	187	121	NA	NA	NA	45.7	16.548	3.363	19.7	Φ15.0	M12xP0.5
	1/4"	1.49	2.1	160	109	NA	NA	NA	45.7	16.548	3.363	19.7	Φ15.0	M12xP0.5
HPB3090	1/4"	0.93	2.0	191	128	NA	NA	NA	28.6	16.637	2.078	11.5	Φ17.0	M12xP0.5
CAN2	1/3"	6.00	1.8	46	35	58	-2.9	-5.5	80.2	23.908	8.952	12.8	Φ14.0	M12xP0.5

上述鏡頭是我司的標準規格, 若不能滿足您的需求, 請洽詢我們業務人員進行客製化評估。

If the above listed lens can not meet in your requirement, please contact our sales representatives for customization inquiry.

レンズカスタマイズ開発を承っております。ご希望のレンズ仕様はリストに記載されない場合は、お気軽に営業窓口にお問い合わせくださいませ。